



GigaSPEED XL GS8E Stranded Cordage Modular Patch Cord, Yellow Jacket, 10 FT

The SYSTIMAX GigaSPEED XL GS8E modular patch cord family is available in multiple colors and in plenum and non-plenum solid conductor options.

SKU:

Price:

Stock: instock

Categories: [Coaxial Cabling Infrastructure](#), [Copper Cabling Infrastructure](#), [Fiber Optic Cabling Infrastructure](#), [Network Infrastructure](#), [Software](#), [Telecom Power Protections](#), [Telephones & Headsets](#)

Product Description

Description

The SYSTIMAX GigaSPEED XL GS8E modular patch cord family is available in multiple colors and in plenum and non-plenum solid conductor options. GigaSPEED XL GS8E cords are available in the Quick-Turn Program for North America customers.; The GigaSPEED XL GS8E modular patch cord family supports the high performance system level requirements built into the GigaSPEED XL cabling solutions. The GigaSPEED XL GS8E family of modular patch cords is available in a wide range of cord types, lengths, colors and configurations.

Features

- Electrical performance guaranteed to meet or exceed the channel specifications of Amendment 1 to
- ISO/IEC 11801:2002 Class EA and ANSI/TIA-568-C.2 Category 6A up to 500 MHz when used as
- part of a GigaSPEED X10D UTP Channel in registered SYSTIMAX installations.
- ETL/cETL listed (except LSZH)
- Can support network line speeds up to at least 10 gigabits per second
- Qualifies for the SYSTIMAX 20-Year Extended Product Warranty and Applications Assurance when
- included as part of a registered SYSTIMAX GigaSPEED X10D channel

Specification Description

Category: 6 Fire Rating: Non-plenum Brand: GigaSPEED XL, SYSTIMAX Cable Type: U/UTP (unshielded)
Family: CPC3312 Connector A: RJ45 plug Connector B: RJ45 plug Conductor Type: Stranded

Tech Info

ISO 9001:2008: Designed, manufactured and/or distributed under this quality management system; RoHS 2002/95/EC: Compliant.

Specifications:

Category	CATEGORY 6
Color	YELLOW
Connector Type	RJ45 TO RJ45
Lengths	10 FT. 3.05 M
Shielded	U/UTP - UNSHIELDED TWISTED PAIR
Type	PATCH CORDS
UNSPSC Code	43223303



Closet Connector Housing (CCH) One Rack Unit, Holds Two CCH Connector Panels

Closet connector housings (CCHs) provide interconnect or cross-connect capabilities between outside plant, riser or distribution cables and opto-electronics

SKU:

Price:

Stock: instock

Categories: [Coaxial Cabling Infrastructure](#), [Copper Cabling Infrastructure](#), [Fiber Optic Cabling Infrastructure](#), [Network Infrastructure](#), [Software](#), [Telecom Power Protections](#), [Telephones & Headsets](#)

Product Description

Description:

Closet connector housings (CCHs) provide interconnect or cross-connect capabilities between outside plant, riser or distribution cables and opto-electronics. Like other LANscape solutions hardware, the housings accept CCH connector panels. In addition, the housings accept CCH cassettes and CCH modules. From fiber and cable routing and strain relief, to port labeling and termination, these housings reduce the risk of error that can disrupt networks.

The units are designed for rack mounting in 19-in (48 cm) racks or optional 23-in (58 cm) equipment racks (1.75-in EIA hole spacing). They are available in rack space options of 1U (two panels, cassettes or modules), 2U (four panels, cassettes or modules), 3U (six panels, cassettes or modules) and 4U (12 panels, cassettes or modules). The 1U, 2U and 3U options feature a slide-out tray and see-through, removable top covers. The CCH-04U features a clear door, removable front and rear enclosures and a platinum-colored interior for maximum visibility and access.

Every CCH housing is shipped complete with strain relief brackets, routing clips and guides, and mounting brackets for proper installation. Documentation labels are provided and components can be added as needed to construct a fiber distribution frame for any application. All housings include a removable tinted polycarbonate front door. All size housings have field-installable lock kits available for both front and rear doors.

All CCH housings can also be upgraded for pigtail splicing to full fiber capacity and easy, modular fiber management through the use of CCH Splice Cassettes (CCH-CS), or for easy, modular fiber management when using field-installable connectors through the use of CCH Slack Cassettes (CCH-CF).

Applications

Carrier Networks, Data Center, Enterprise Networks

Features

- Interconnect and cross-connect capability
- Ideal for field connectorisation
- Removable, translucent top covers (1U, 2U, 3U), removable rear cover (4U)
- Visibility and ease of access for installation, testing, and troubleshooting
- Internal and external strain-relief options
- Flexibility for installation and moves, adds, and changes (MACs)
- Accepts panels, modules, and cassettes
- Variety of field-termination options
- Adaptable to use as a modular splice housing
- Splices are stored and protected in a footprint

Specification Description

Meets ANSI/TIA/EIA-568A and 606

Tech Info

Approval and Listings: Meets ANSI/TIA/EIA-568A and 606; Free of hazardous substances according to RoHS 2002/95/EG

Specifications:

Connectorized Fibers 12/48

Loaded	UNLOADED
Type	RACK MOUNT
UNSPSC Code	43223337
