



Fluke 287 True RMS Electronics Logging Multimeter

SKU:

Price:

Stock: instock

Categories: [Best Seller](#), [Fluke Product](#)

Product Description

Key features

Equipped with new functionality

- Now compatible with Fluke Connect mobile app and all Fluke FC enabled test tools with optional ir3000 FC infrared connector (sold separately).
- Let your team see what you see in an instant with ShareLive™ video call (requires Fluke Connect mobile app and ir3000 FC wireless connector).
- TrendCapture quickly graphically displays logged data session to quickly determine whether anomalies may have occurred.
- Limited lifetime warranty.

Product overview: Fluke 287 True-RMS Electronics Logging Multimeter

Now compatible with Fluke Connect® Mobile App The Fluke 287 True-rms Electronics Logging Multimeter with TrendCapture quickly documents design performance and graphically displays what happened. Its unique logging and graphing capabilities mean you no longer need to download logged readings to a PC to detect a trend. The Fluke 287 packs more accuracy and convenience into a handheld multimeter than ever before:

- Zoom on trend provides unprecedented ability to view and analyze TrendCapture data; zoom in up to 14 times.
- Selectable AC filter (smoothing mode) helps display a steadier reading when the input signal is changing rapidly or noisy.
- Adjustable recording and auto hold thresholds, specify a percentage change in the readings that begins a new event.

- Large 50,000 count, 1/4 VGA display with white backlight. Multiple sets of measurement information can be simultaneously displayed at the same time.
- Logging function with expanded memory for unattended monitoring of signals over time. Using on-board TrendCapture users can graphically review logged readings without needing a PC. Store up to 15,000 recorded events.
- On board help screens for measurement functions.
- Saved measurements allow you to name and recall measurements made in the field.
- Multi-lingual interface.
- Multiple logging sessions possible without download.
- 0.025% basic DC accuracy.
- 100 kHz AC bandwidth.
- Real time clock for automatic time stamping of saved readings.
- True-RMS AC voltage and current for accurate measurements on complex signals or non-linear loads. AC bandwidth specified to 100 kHz.
- Measure up to 10 A (20 A for 30 seconds).
- 100 mF capacitance range.
- Temperature function.
- Relative mode to remove test lead resistance from low ohms or capacitance measurements. • Peak capture to record transients as fast as 250 μ s.
- Premium test leads and alligator clips included.
- Amp jack plugs included.
- Optional FlukeView forms enable you to document, store and analyze individual readings or a series of measurements, then convert them into professional-looking documents.
- Optional magnetic hanger allows you to hang the meter for easy viewing while freeing your hands to focus on the job.

Specifications: Fluke 287 True-RMS Electronics Logging Multimeter

Specifications

Function

DC volts	Range / resolution	50.000 mV, 500.00 mV, 5.0000 V, 50.000 V, 500.00 V, 1000.0 V
	Basic accuracy	0.025%
AC volts	Range / resolution	50.000 mV, 500.00 mV, 5.0000 V, 50.000 V, 500.00 V, 1000.0 V
	Basic accuracy	0.4% (True-RMS)
DC current	Range / resolution	500.00 μ A, 5000.0 μ A, 50.000 mA, 400.00 mA, 5.0000 A, 10.000 A
	Basic accuracy	0.05%
AC current	Range / resolution	500.00 μ A, 5000.0 μ A, 50.000 mA, 400.00 mA, 5.0000 A, 10.000 A
	Basic accuracy	0.6% (True-RMS)
Temperature (excluding probe)	Range / resolution	-200.0°C to 1350.0°C (-328.0°F to 2462.0°F)
	Basic accuracy	1.0%

Resistance	Range / resolution 500.00 Ω , 5.0000 k Ω , 50.000 k Ω , 500.00 k Ω , 5.0000 M Ω , 50.00 M Ω , 500.0 M Ω Basic accuracy 0.05%
Capacitance	Range / resolution 1.000 n, 10.00 nF, 100.0 nF, 1.000 μ F, 10.00 μ F, 100.0 μ F, 1000 μ F, 10.00 mF, 100 mF Basic accuracy 1.0%
Frequency	Range / resolution 99.999 Hz, 999.99 Hz, 9.9999 kHz, 99.999 kHz, 999.99 kHz Basic accuracy 0.005%
Connectivity	Optional infrared connector via Fluke ir3000 FC
General Specifications	
Maximum voltage between any terminal and earth ground	1000 V
Battery type	6 AA alkaline batteries, IECLR6
Battery life	100 hours minimum, 200 hours in logging mode
Temperature	Operating -20°C to 55°C Storage -40°C to 60°C
Relative humidity	0 to 90% (0 to 37°C), 0 to 65% (37°C to 45°C), 0 to 45% (45°C to 55°C)
Electromagnetic compatibility	EMC EN61326–1
Vibration	Random vibration per MIL-PRF-28800F Class 2
Shock	1 meter drop per IEC/EN 61010–1 3rd Edition
Size (H x W x L)	22.2 x 10.2 x 6 cm (8.75 x 4.03 x 2.38 in)
Weight	870.9 g (28 oz)
Multiple on screen displays	Yes
True-RMS AC bandwidth	100 kHz
dBV/dBm	Yes
DC mV resolution	1 μ V
Megohm range	Up to 500 M Ω
Conductance	50.00 nS
Continuity beeper	Yes
Battery/fuse access	Yes/Yes
Elapse time clock	Yes
Time of day clock	Yes
Min-max-avg	Yes
Peak	250 μ s
Duty cycle	0.01% to 99.99%
Pulse width	0.025 ms, 0.25 ms, 2.5 ms, 1250.0 ms
Hold	Yes
Isolated optical interface	Yes
Auto/touch hold	Yes

Reading memory	Yes
Log to PC	Yes
Interval/event logging	Yes
Logging memory	Up to 10,000 readings
Wireless connectivity (optional)	Yes
